




Overzicht dome camera's

Z-BEN® award-winning leader in CCTV products				
Artikel nummer	Full HD	vc525z2	vc525z2p	vc550z2
	5,0 MP	vc525z5	vc525z5p	vc550z5
Camera type		Kogeldome	Kogeldome	Buitendome
Sensor	Full HD	1/2.8" SONY 2,4 MP C-MOS	1/2.8" SONY 2,4 MP C-MOS	1/2.8" SONY 2,4 MP C-MOS
	5,0 MP	1/2.5" Aptina 5,0 MP C-MOS	1/2.5" Aptina 5,0 MP C-MOS	1/2.5" Aptina 5,0 MP C-MOS
Aantal pixels	Full HD	1920 x 1080	1920 x 1080	1920 x 1080
	5,0 MP	2592 x 1944	2592 x 1944	2592 x 1944
Objectief (IR gecorrigeerd)		3,6 mm	3,6 mm	2,8-12 mm
D/N IR-filter		Ja	Ja	Ja
Lichtgevoeligheid		0 Lux, IR-LED's aan	0 Lux, IR-LED's aan	0 Lux, IR-LED's aan
IR	LED's	24 x 5 mm	1 x Power Array	30 x 5 mm
	Bereik	Maximaal 30 meter	Maximaal 30 meter	Maximaal 30 meter
IP	Stream	H.264 / Dual stream	H.264 / Dual stream	H.264 / Dual stream
	Protocol	Onvif Profile S 2.3	Onvif Profile S 2.3	Onvif Profile S 2.3
Hoofd stream	Full HD	25 BPS @ 1080p/720p/D1	25 BPS @ 1080p/720p/D1	25 BPS @ 1080p/720p/D1
	5,0 MP	25 BPS @ 1080p	25 BPS @ 1080p	25 BPS @ 1080p
		12 BPS @ 5,0 MP	12 BPS @ 5,0 MP	12 BPS @ 5,0 MP
Sub stream	Full HD	25 BPS @ D1/CIF	25 BPS @ D1/CIF	25 BPS @ D1/CIF
	5,0 MP			
Ethernet		10/100M, RTSP/FTP/PPOE/ DHCP/DDNS/UPNP	10/100M, RTSP/FTP/PPOE/ DHCP/DDNS/UPNP	10/100M, RTSP/FTP/PPOE/ DHCP/DDNS/UPNP
Voeding	PoE	Ja	Ja	Ja
	12 VDC	Ja	Ja	Ja
Behuizing		Metaal	Metaal	Metaal
Montage		Opbouw	Opbouw	Opbouw
Omgevingsbestendigheid		IP66	IP66	IP66
Afmetingen ø*H (mm)		ø110*75	ø130*120	ø130*110
Gewicht in grammen		430	560	840

(Versie 1.5 van 24 augustus 2015)