

# CONCEALED DOME CAMERA


## D1 Series



This concealed camera is specially designed for high level security or concealed monitoring applications such as bank, ATM machine, airport, museum, detective, spy and home security.

## FEATURES

- ▶ Camera lens covered by the special patented front cover
- ▶ Ceiling mount spot light outlook with camera embedded
- ▶ Easy adjustable view angle
- ▶ 1/3" color CCD sensor for clear video output



## SPECIFICATIONS

Model Number		CC-MS-D1	CC-MS2-D1	CC-HS2-D1
Scanning System	NTSC	525 lines 2:1 interlace	525 lines 2:1 interlace	
	PAL	625 lines 2:1 interlace	625 lines 2:1 interlace	
Scanning Frequency	NTSC	15,734Hz(H) , 60Hz(V)	15,734Hz(H) , 60Hz(V)	
	PAL	15,625Hz(H) , 50Hz(V)	15,625Hz(H) , 50Hz(V)	
Effective Pixel	NTSC	510(H) x 492(V)	510(H) x 492(V)	768(H) x 494(V)
	PAL	500(H) x 582(V)	500(H) x 582(V)	752(H) x 582(V)
Electronic Shutter	NTSC	1/60-100,000sec.	1/60-100,000sec.	
	PAL	1/50-100,000sec.	1/50-100,000sec.	
Image Device	1/3" SONY Super HAD CCD		1/3" SONY Super HAD CCD	
Horizontal Resolution	420 TV lines		480 TV lines enhanced	560 TV lines enhanced
Sensitivity	0.2Lux		0.01Lux	
Signal to Noise	More than 48dB		More than 52dB	
Gain Control	AGC		AGC(+18 Db)	
White Balance	Auto 2500-9500 <sup>0</sup> K		Auto 2500-9500 <sup>0</sup> K	
Sense-UP times	-		Max 32 times	
DNR	-		Built-in DNR (Digital Noise Reduction)	
BLC	Auto		Auto	
Gamma Correction	0.45		0.45	
SYNC System	Internal		Internal	
Lens/Focus point	3.6mm (Optional 4.3mm, 6mm)		3.6mm (Optional 4.3mm, 6mm)	
Video Output	1.0 Vp-p 75 Ohm		1.0 Vp-p 75 Ohm	
Power Requirement (±10%)	DC12V, 500mA		DC12V, 500mA	
Power Consumption (±10%)	100mA		100mA	
Operation Temp.	Working: -10~+50 <sup>0</sup> C, Storage: -30~+70 <sup>0</sup> C, Humidity:0~95%RH			
Dimension(mm]	∅ 100 x 90			
Weight( N.W]	235g			